

 POLARIS

SPORTSMAN[®]




POLARIS[®]



SPORTSMAN ACE 570



SPORTSMAN 570 / Touring
(Avail. with EPS)



SPORTSMAN 850 / Touring



SPORTSMAN 1000XP / Touring
(Avail. with EPS)



SCRAMBLER 1000 XP

Engine Type	4-Stroke DOHC Single Cylinder	4-Stroke DOHC Single Cylinder	4-Stroke SOHC Twin Cylinder	4-Stroke SOHC Twin Cylinder	4-Stroke SOHC Twin Cylinder
Displacement	567cc	567cc	850cc (High Output)	952cc	952cc
Fuel System	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
Cooling	Liquid	Liquid	Liquid	Liquid	Liquid
Transmission / Final Drive	Automatic PVT P/R/N/L/H; Shaft	Automatic PVT P/R/N/L/H; Shaft	Automatic PVT P/R/N/L/H; Shaft	Automatic PVT P/R/N/L/H; Shaft	Automatic PVT P/R/N/L/H; Shaft
Drive System	On-Demand True AWD/2WD	On-Demand True AWD/2WD	On-Demand True AWD/2WD	High Performance Close Ratio, On Demand True AWD / 2WD.	High Performance Close Ratio, On Demand True AWD / 2WD.
Engine Braking System / Active Descent Control	No / No	No / No	Standard / No	Standard / Standard	No / No
Front Suspension	MacPherson Strut 208 mm Travel	MacPherson Strut 208 mm Travel	Dual A-Arm, 230 mm Travel	Dual A-Arm, 230 mm Travel	Dual A-Arm, 230 mm Travel
Rear Suspension	Dual A-Arm IRS 241 mm Travel	Dual A-Arm, IRS 241 mm Travel	Dual A-Arm, Rolled 260 mm Travel	Dual A-Arm, Rolled 260 mm Travel	Dual A-Arm, Rolled 260 mm Travel
Front / Rear Brakes	4-Wheel Hydraulic Disc	Single Lever 4-Wheel Hydraulic Disc Hydraulic Rear Foot Brake	Single Lever 4-Wheel Hydraulic Disc Hydraulic Rear Foot Brake	Single Lever 4-Wheel Hydraulic Disc Hydraulic Rear Foot Brake	Single Lever 4-Wheel Hydraulic Disc Hydraulic Rear Foot Brake
Parking Brakes	Park in Transmission	Park in Trans./Lockable Hand Lever	Park in Trans./Lockable Hand Lever	Park in Trans./Lockable Hand Lever	Park in Trans./Lockable Hand Lever
Front Tyres	25 x 8-12; 489	25 x 8-12; 489	26 x 8-14; Maxxis	26 x 8-14; PXT	26 x 8-14; 489 II
Rear Tyres	25 x 10-12; 489	25 x 10-12; 489	26 x 10-14; Maxxis	26 x 11-14; PXT	26 x 10-14; 489 II
Wheels	Stamped Steel	Stamped Steel	Stamped Steel / Cast Aluminium	Cast Aluminium	Cast Aluminium
Wheelbase	1560 mm	1290 mm	1448 mm	1346 mm	1346 mm
Overall Vehicle Size (LxWxH)	2290 x 1220 x 1730 mm	3110 x 1220 x 1220 mm	2200 x 1210 x 1480 mm	2100 x 1210 x 1210 mm	2080 x 1230 x 1230 mm
Ground Clearance	260 mm	280 mm	2850 mm	290 mm	290 mm
Seat Height	N.A.	860 mm	940 mm	940 mm	890 mm
Fuel Capacity	20 L	17 L	20 L	20 L	20 L
Front / Rear Rack / Box Capacity	55 Kg / 110 Kg	41 Kg / 82 Kg	55 Kg / 110 Kg	55 Kg / 110 Kg	11.3 Kg / 22.7 Kg
Payload Capacity	261 Kg	220 Kg / 230 Kg (EPS) / 330 Kg (Touring)	261 Kg	261 Kg	131 Kg
Hitch Towing Rating	680 Kg	556 Kg	680 Kg	680 Kg	680 Kg
Hitch / Type	Standard / 1.25" Receiver	Standard / 1.25" Receiver	Standard / 1.25" Receiver	Standard / 1.25" Receiver	Standard / 1.25" Receiver
Cargo System	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
Lighting	Dual 50w Low Beam Bumper Lights, Dual Brake / Taillights	Dual 50W Low Beam Bumper Lights, Single 50w High Beam pod Light; Dual Brake / Taillights	Triple 50W High Beam, Dual 50w Low Beam Headlights; Dual Brake / Taillights	Triple 50W High Beam, Dual 50w Low Beam Headlights; Dual Brake / Taillights	Dual Hi/Low Beam (50w/50w) White LED; Hi/Low Beam; Single Rear Taillight
Electronic Power Steering	N.A.	EPS (Optional)	N.A.	Standard	Standard
Winch	N.A.	N.A.	N.A.	Polaris HD 2500LB	N.A.
Box Dimensions	460 x 890 x 100mm	N.A.	N.A.	N.A.	N.A.
Instrumentation	Digital Gauge, Analog Speedometer, Odometer, Tachometer, 2 Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Low Battery, Hi-Temp Light, Clock, DC Outlet	Digital Gauge, Analog Speedometer, Odometer, Tachometer, 2 Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Low Battery, Hi-Temp Light, Clock, DC Outlet	Digital Gauge, Analog Speedometer, Odometer, Tachometer, 2 Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Low Battery, Hi-Temp Light, Clock, DC Outlet	Digital Gauge, Analog Speedometer, Odometer, Tachometer, 2 Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Low Battery, Hi-Temp Light, Clock, DC Outlet	Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Clock, Service Time, Diagnostic Indicator, Gear Indicator, Fuel Gauge, Hi-Temp/Low-Batt Lights, DC Outlet
Colours	570 cc 	Std EPS Touring 	Std Touring 	L.E Std Touring 	

Blue Fire
 Voodoo Blue
 White Lightning
 Sage Green
 Polaris Pursuit Camo
 Bronze Mist
 Sunset Red
 Titanium Matte Metallic

For more information and specifications visit
www.polarissa.co.za

Polaris South Africa supports responsible riding. For your safety, always wear a helmet, eye protection, protective clothing and never carry passengers unless the ATV or Side x Side has been designed by the manufacturer specifically for that purpose. Models are for riders aged 16 years and older. Contact your dealer for colour options. Images are for illustration purposes only. Certain models may vary from those shown. E&OE.

POLARIS

